











ABOUT

Type of manufacture	Tufted	ISO 2424
Width	400 cm / 500 cm	EN 14159
Type of surface	Loop pile	ISO 2424
Pile material	100% wool	ISO 2424
Backing	Feltback	ISO 2424
Pile weight	± 975 g/m ²	ISO 8543
Total weight	± 2080 g/m ²	ISO 8543
Pile height	± 4,0 mm	ISO 1766
Total height	± 6,4 mm	ISO 1765

APPLICATION

Use classification	23 residential use / 32 commercial use		EN 1307 ISO 10361
Suitability for use on stairs	Suitable for residential use		EN 1307 ISO 12951
Suitability for castor chair	Suitable for residential use		EN 1307 ISO 4918
Antistatic behaviour	≤ 2.0 kV at 25% RH		ISO 6356
Thermal resistance	≤ 0,13 m ² K/W		ISO 8302
Burning behaviour	C _{fl} -s1		EN 11925-2 ISO 9239-2
Colourfastness to light	≥ 5		EN 1307 ISO 105-B02
Impact sound insulation	Δ L _w ≥ 20 dB		EN 717-2 ISO 10140-3
Comfortclass	LC3		EN 1307 EN 8543
Slip resistance	DS		EN 14041 EN 13893

