

ABOUT

Type of manufacture	Woven	ISO 2424
Dimension	50 x 50 cm	EN 14159
Content	16 pieces (4m ²)	
Type of surface	Loop pile	ISO 2424
Pile material	100% sisal	ISO 2424
Backing	PVC	ISO 2424
Pile weight	± 1700 g/m ²	ISO 8543
Total weight	± 2200 g/m ²	ISO 8543
Pile height	± 5,0 mm	ISO 1766
Total height	± 7,0 mm	ISO 1765

APPLICATION

Use classification	23 residential use / 32 commercial use		EN 1307 ISO 10361
Suitability for use on stairs	Not suitable		
Suitability for castor chair	Suitable for residential and commercial use		EN 1307 ISO 4918
Antistatic behaviour	≤ 2.0 kV at 25% RH		ISO 6356
Thermal resistance	≤ 0,11 m ² K/W		ISO 8302
Burning behaviour	C _{fl} -s1		EN 11925-2 ISO 9239-2
Colourfastness to light	≥ 5		EN 1307 ISO 105-B02
Impact sound insulation	Δ L _w ≥ 10 dB		EN 717-2 ISO 10140-3
Comfortclass	LC1		EN 1307 EN 8543
Slip Resistance	DS		EN 14041 EN 13893

*Fire class Cfl-s1 applies only on a non-combustible subfloor

