



ABOUT

| | | |
|---------------------|-------------------------|----------|
| Type of manufacture | Woven | ISO 2424 |
| Width | 400 cm / 500 cm | EN 14159 |
| Type of surface | Loop pile | ISO 2424 |
| Pile material | 100% undyed wool | ISO 2424 |
| Backing | Actionback | ISO 2424 |
| Pile weight | ± 650 g/m ² | ISO 8543 |
| Total weight | ± 2000 g/m ² | ISO 8543 |
| Pile height | ± 2,5 mm | ISO 1766 |
| Total height | ± 3,5 mm | ISO 1765 |

APPLICATION

| | | | |
|-------------------------------|--|---|-------------------------|
| Use classification | 22 residential use / 32 commercial use |  | EN 1307 ISO 10361 |
| Suitability for use on stairs | Suitable for residential use |  | EN 1307 ISO 12951 |
| Suitability for castor chair | Suitable for residential use |  | EN 1307 ISO 4918 |
| Antistatic behaviour | ≤ 2.0 kV at 25% RH |  | ISO 6356 |
| Thermal resistance | ≤ 0,10 m ² K/W |  | ISO 8302 |
| Burning behaviour | C _{fl} -s1 |  | EN 11925-2 ISO 9239-2 |
| Colourfastness to light | ≥ 5 |  | EN 1307 ISO 105-B02 |
| Impact sound insulation | Δ L _w ≥ 10 dB |  | EN 717-2 ISO 10140-3 |
| Comfortclass | LC1 |  | EN 1307 EN 8543 |
| Slip Resistance | DS |  | EN 14041 EN 13893 |



Scan QR-code to request samples

