

## ABOUT

|                     |                          |          |
|---------------------|--------------------------|----------|
| Type of manufacture | Tufted                   | ISO 2424 |
| Width               | 400 cm                   | EN 14159 |
| Type of surface     | Cut pile                 | ISO 2424 |
| Pile material       | 100% wool                | ISO 2424 |
| Backing             | Feltback                 | ISO 2424 |
| Pile weight         | $\pm 2300 \text{ g/m}^2$ | ISO 8543 |
| Total weight        | $\pm 2750 \text{ g/m}^2$ | ISO 8543 |
| Pile height         | $\pm 18,0 \text{ mm}$    | ISO 1766 |
| Total height        | $\pm 19,0 \text{ mm}$    | ISO 1765 |

## APPLICATION

|                               |                                           |                                                                                       |                         |
|-------------------------------|-------------------------------------------|---------------------------------------------------------------------------------------|-------------------------|
| Use classification            | 23 residential use / 31 commercial use    |  | EN 1307   ISO 10361     |
| Suitability for use on stairs | Not suitable                              |                                                                                       | EN 1307   ISO 12951     |
| Suitability for castor chair  | Not suitable                              |                                                                                       | EN 1307   ISO 4918      |
| Antistatic behaviour          | $\leq 2.0 \text{ kV at } 25\% \text{ RH}$ |  | ISO 6356                |
| Thermal resistance            | $\leq 0,15 \text{ m}^2 \text{ K/W}$       |  | ISO 8302                |
| Burning behaviour             | $E_{fl}$                                  |  | EN 11925-2   ISO 9239-2 |
| Colourfastness to light       | $\geq 4$                                  |  | EN 1307   ISO 105-B02   |
| Impact sound insulation       | $\Delta L_w \geq 25 \text{ dB}$           |  | EN 717-2   ISO 10140-3  |
| Comfortclass                  | LC5                                       |  | EN 1307   EN 8543       |
| Slip Resistance               | DS                                        |  | EN 14041   EN 13893     |



Scan QR-code to  
request samples

